

# Tape Specifications

## Warning Tape - “Caution Electric Cable below”

Code	d	Length	Thickness	Pack Qty
WT	150mm	365Mtrs	50microns	1

Used to protect and identify underground utility lines. Made from a high quality low density polyethylene this tape has a life expectancy of over 50 years

Material: Virgin Grade Polyethylene m (LDPE)  
 Soil Tolerance: pH 2.5 - pH 11.0  
 Tensile Strength: 150%  
 Elongation Break: 10 MPA



## Waterproof Cloth Tape (aka Duct tape / Gaffer tape)

Code	d	Length	Thickness	Pack Qty
GT	50mm	50Mtrs	0.17mm	1

This tape has a polythene coating on a cloth backing giving strength, waterproofing and tear ability. Great for sealing, bundling, masking, a good all rounder.

Material: Cloth with polythene coating  
 Tensile Strength: 35 N/cm  
 Adhesion to backing: 2.5 N/cm  
 Adhesion to steel: 4.0 N/cm



## Self Amalgamating Tape

Code	d	Length	Thickness	Pack Qty
AT	19mm	10Mtrs	0.5mm	1

Very good electrical and physical properties, amalgamates quickly when applied under tension providing a void-free homogeneous wrapping. Very good water and ozone resistance

Material: based on polyisobutylene interleaved with plastic film  
 Tensile Strength: 100 N/cm  
 Elongation Break: 650%




## Hazard Warning Tape

Code	d	Length	Thickness	Pack Qty
HT	50mm	33Mtrs	0.1mm	1

Complies with OSHA requirements this tapes has a very high tack suitable even for concrete and timber. Designed for the markings of walkways or demarcation of dangerous zones etc.

Material: Heavy Duty PVC / rubber adhesive  
 Tensile Strength: 7.2 N/cm  
 Elongation Break: 200%



# Tape Specifications cont.

## PVC Insulation Tape

Code	d	Length	Thickness	Pack Qty
PT33	19mm	33Mtrs	0.13mm	10

For use as electrical insulation on joints and splices. Excellent conformability and high elongation at break. Self extinguishing and flame retardant to BS3924 / EN60454

Material: PVC film coated with aggressive solvent based rubber resin adhesive  
Tensile Strength: 24.6 N/cm  
Elongation Break: 150%  
Adhesion: 2.0 N/ 10mm



## Barrier Tape

Code	d	Length	Thickness	Pack Qty
BT	75mm	500Mtrs	30 Micron	1

To mark areas of danger commonly used on construction sites and no go areas. Easy to tear and tie off.

Material: LDPE

