

## BPE - ABS HINGED LID ENCLOSURES

### Description:

Robust opaque ABS hinged lid enclosure with a hinged door secured by triangle key lock. Supplied with a galvanised steel backplate pre-installed, matching key set, wall-mounting kit, and appropriate fixing screws.

### IP Rating:

IP65

### IK Rating:

IK10

### RAL Colour:

RAL 7035



## ADDITIONAL INFORMATION

| Code      | External    |            |            | Internal    |            |            | Number of Locks | Min/Max Temp                    | Certifications & Standards                                      |
|-----------|-------------|------------|------------|-------------|------------|------------|-----------------|---------------------------------|---|
|           | Height (mm) | Width (mm) | Depth (mm) | Height (mm) | Width (mm) | Depth (mm) |                 |                                 |   |
| BPE302013 | 300         | 200        | 130        | 247         | 143        | 110        | 2               | -25 - +60°C<br>Glow wire: 650°C | CE<br>UKCA<br>IEC 60670-24:2011<br>IEC60670-1:2002<br>AMD1:2011 |
| BPE352515 | 350         | 250        | 150        | 297         | 192        | 130        | 2               |                                 |   |
| BPE403017 | 400         | 300        | 170        | 350         | 243        | 150        | 2               |                                 |   |
| BPE403022 | 400         | 300        | 220        | 350         | 243        | 200        | 2               |                                 |   |
| BPE503519 | 500         | 350        | 190        | 447         | 290        | 170        | 2               |                                 |   |
| BPE504024 | 500         | 400        | 240        | 450         | 341        | 220        | 2               |                                 |   |
| BPE604020 | 600         | 400        | 200        | 545         | 342        | 180        | 2               |                                 |   |
| BPE605022 | 600         | 500        | 220        | 547         | 442        | 200        | 2               |                                 |   |
| BPE705025 | 700         | 500        | 250        | 647         | 442        | 230        | 2               |                                 |   |
| BPE806026 | 800         | 600        | 260        | 747         | 542        | 240        | 3               |                                 |   |

