

## HSP - HEATSHRINK PACKS

### Description:

15 piece pack (3 x 250mm of each colour) of Heatshrink, ideal for insulation, wire bundling and mechanical protection

### Material:

125H Halogen-free flame retardant heat shrink, manufactured from polyolefin.

The content of lead (Pb), Cadmium (Cd), Mercury (Hg), hexavalent chromium (Cr 6+), polybromobiphenyl (PBB), polybromine biphenyl ether (PBDE) and other environmental substances meet the requirements of the European Union (EU) 2015/863 (RoHS2.0) Chlorine. The (Cl) and bromine (Br) content meet the environmental requirements of Japan SONY-SS-00259.



## OTHER ADDITIONAL INFORMATION

| Codes  | Pre Shrinkage Size (mm) |                | Retraction after the dimension (mm) |                | Scope of Application |
|--------|-------------------------|----------------|-------------------------------------|----------------|----------------------|
|        | Inner Size              | Wall Thickness | Maximum Inner Diameter              | Wall Thickness |                      |
| HSP48  | 5.0±0.2                 | 0.28±0.05      | ≤2.30                               | 0.56±0.10      | 2.35~4.00            |
| HSP64  | 6.5±0.2                 | 0.28±0.05      | ≤3.00                               | 0.56±0.10      | 3.10~5.40            |
| HSP95  | 9.5±0.3                 | 0.30±0.08      | ≤4.50                               | 0.56±0.10      | 4.7~8.0              |
| HSP128 | 12.8±0.3                | 0.30±0.08      | ≤6.00                               | 0.56±0.10      | 6.2~11.0             |
| HSP191 | 19.1±0.5                | 0.35±0.10      | ≤9.00                               | 0.70±0.10      | 9.3~17.0             |
| HSP254 | 26.0±0.5                | 0.45±0.12      | ≤12.50                              | 0.90±0.15      | 12.8~24.0            |
| HSP380 | 41.5±1.0                | 0.50±0.12      | ≤20.00                              | 1.00±0.15      | 21~39                |
| HSP500 | ≥50                     | 0.50±0.15      | ≤25.00                              | 1.10±0.20      | 26~49                |