

**SST - A2 STAINLESS STEEL CABLE TIES****Description:**

Tie Material: Stainless Steel A2 (304)

Description: Roller Ball Lock Type

This grade of stainless steel offers strong abrasion resistance, good resistance to corrosion with reliably low levels of distortion. Our A2 Stainless Steel Cable Ties offer an economical alternative to our A4 Certified Stainless Tie Range.



Code	Width (mm)	Thickness (mm)	Length (mm)	Tensile (N)
SST46200	4.6±0.2	0.25±0.02	200±2	1200
SST46300	4.6±0.2	0.25±0.02	300±2	1200
SST46360	4.6±0.2	0.25±0.02	360±2	1200
SST46520	4.6±0.2	0.25±0.02	520±2	1200

**MT - 201 STAINLESS STEEL TIES****Description:**

Tie Material: Stainless Steel 201

Description: Roller Ball Lock Type

201 Stainless Steel offers exceptional tensile strength at the most budget-friendly price point.



Code	Width (mm)	Thickness (mm)	Length (mm)	Tensile (N)
MT46200	4.6±0.2	0.25±0.02	200±2	1200
MT46300	4.6±0.2	0.25±0.02	300±2	1200
MT46360	4.6±0.2	0.25±0.02	360±2	1200

## CTSS/CTSSB - A4 STAINLESS STEEL CABLE TIES

### Description:

Tie & Base Material: Stainless Steel SS316 (A4) BS EN 62275

Self Colour Operating Temperature: -80 to 500°C

Epoxy Black Operating Temperature: -80 to 150°C

Description: Roller Ball Lock Type

Marine Grade quality typically for outdoor use and chemically harsh environments with a higher level of corrosion resistance. Contains Molybdenum which is highly ductile and has an extremely high melting point

## Fully Tested & Certified



• Tested for:  
2 Hours

• Temperature:  
930°C



Code	Width (mm)	Thickness (mm)	Length (mm)	Tensile (N)
CTSS150	4.6±0.2	0.25±0.02	150±2	1200
CTSS200	4.6±0.2	0.25±0.02	200±2	1200
CTSS300	4.6±0.2	0.25±0.02	300±2	1200
CTSS360	4.6±0.2	0.25±0.02	360±2	1200
CTSS520	7.9±0.2	0.25±0.02	520±2	1600
CTSSB200	4.6±0.2	0.3-0.4mm	200±2	800
CTSSB300	4.6±0.2	0.3-0.4mm	300±2	800
CTSSB360	4.6±0.2	0.3-0.4mm	360±2	800
CTSSB520	7.9±0.2	0.3-0.4mm	520±2	1200