PPC, PPCG, PPHC - PP FLEXIBLE CONDUIT & ACCESSORIES

Description:
Easy installation for residential and commercial buildings. Used inside/outside concrete, and under floor installations.

Material: Polypropylene
Standard: EN 61386-22
Operating Temperature: -25°C/+60°C
Flammability Class: UL94 HB

CE ROHS Compliant

OTHER ADDITIONAL INFORMATION

PP Conduit Coils

Code	Colour	Size (mm)	Length (m)	Inside Dia. (mm)	Outside Dia. (mm)
PPC20-50B	Black	20	50	14.20	20.00
PPC25-50B	Black	25	50	18.10	25.00
PPC32-50B	Black	32	50	24.20	32.00
PPC20-50W	White	20	50	14.20	20.00
PPC25-50W	White	25	50	18.10	25.00
PPC32-50W	White	32	50	24.20	32.00

PP Hinged Glands/Adaptors

Code	Colour	TD (mm)	TL (mm)	H (mm)
PPCG20B	Black	20.00	13.00	43.00
PPCG25B	Black	25.00	13.00	43.00
PPCG20W	White	20.00	13.00	43.00
PPCG25W	White	25.00	13.00	43.00



PP Hinged Clips

Code	Colour	A (mm)	B (mm)	H (mm)
PPHC20B	Black	13.00	31.50	32.00
PPHC25B	Black	13.00	35.00	37.00
PPHC32B	Black	14.00	42.00	42.00
PPHC20W	White	13.00	31.50	32.00
PPHC25W	White	13.00	35.00	37.00
PPCH32W	White	14.00	42.00	42.00



Deligo Ltd. 2024 - This document is provided to the public for information purposes only and is subjected to change without notice. Deligo Ltd make no promise of the document keeping the information contained within.