

METAL WORKING FLUID T515

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: METAL WORKING FLUID

Article number: T515

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC25: Metal working fluids.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial

Unit 31, Kyle Road Industrial Estate

Irvine Ayrshire KA12 8LE

Tel +44 (0) 1294 311 066

Email technical@tygrisindustrial.com

Further information obtainable from:

Technical Department

1.4 Emergency telephone

number:

Tel +44 (0) 1294 311 066

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: EUH208

Most important adverse

effects:

Contains pine oils. May produce an allergic reaction.

2.2. Label elements

Hazard Statements: EUH208: Contains pine oils. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance



METAL WORKING FLUID

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DISTILLATES(PETROLEUM), HYDROTREATED HEAVY PARAFFINIC - REACH registered number(s): 01-2119484627-25

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-157-1	64742-54-7	-	Asp. Tox. 1: H304	30-50%

PINE OILS

-	-	Flam. Liq. 3: H226; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic	<1%
		2: H411; Asp. Tox. 1: H304	

SECTION 4: First aid measures

4.1. Description of first aid measures

Wash immediately with plenty of soap and water. Skin contact: Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation at the site of contact.

Eye contact: There may be irritation and redness. Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Continuous skin contact may cause skin sensitivity and dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special

Not applicable.

treatment:

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to

cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.



Version 2 Page 2 to 7

METAL WORKING FLUID T515

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leakside up

to prevent the escape of liquid. Mark out the contaminated area with signs and prevent

access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage

room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC25: Metal working fluids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DISTILLATES(PETROLEUM), HYDROTREATED HEAVY PARAFFINIC

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	5 mg/m3	-	-	-

PINE OILS

EU 556mg/m3 850mg/m3	-	-
----------------------	---	---

DNEL/PNEC Values

PINE OILS

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	5mg/kg	Workers	Local
DNEL	Inhalation	5.8mg/m3	Workers	Local
DNEL	Dermal	2.5 mg/kg	Consumers	Local
DNEL	Inhalation	1.25 mg/m3	Consumers	Local
PNEC	Fresh water	62ug/l	-	-
PNEC	Marine water	6.2ug/l	-	-
PNEC	Fresh water sediments	0.442	-	-
PNEC	Marine sediments	0.044mg/kg	-	-
PNEC	Soil	0.052mg/kg	-	-
PNEC	Oral	16.6mg/kg food	-	-

8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves. Eye protection: Safety glasses. Skin protection: Protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid Colour: Dark green

Perceptible odour Odour:

Solubility in water: Insoluble

9.2. Other information

Other information: No data available.

Version 2

Page 4 to 7

SAFETY DATA SHEET



METAL WORKING FLUID T515

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition

products:

In combustion emits toxic fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC

DERMAL	RBT	LD50	>5000	mg/m3
ORAL	RAT	LD50	>5000	mg/m3
VAPOURS	RAT	LD50	>5000	mg/m3

PINE OILS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>3200	mg/kg
VAPOURS	RAT	4H LC50	4.76	mg/l

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: Not applicable.



METAL WORKING FLUID

SECTION 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

DISTILLATES(PETROLEUM), HYDROTREATED HEAVY PARAFFINIC

Daphnia magna	96H LC50	110	mg/l
FISH	72H ErC50	110	mg/l

PINE OILS

ALGAE	72H ErC50	68	mg/l
DAPHNIA	48H EC50	73	mg/l
FISH	96H LC50	62-80	mg/l

12.2. Persistence and degradability

Persistence and degradability:

Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recycling/reclamation of organic substances which are not used as solvents **Recovery operations:**

(including composting and other biological transformation processes).

Arrange for collection by specialised disposal company. Disposal of packaging:

The user's attention is drawn to the possible existence of regional or national regulations NB:

regarding disposal.

Version 2

SAFETY DATA SHEET



METAL WORKING FLUID T515

SECTION 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group:

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical safety assessment

Chemical safety A chemical safety assessment has not been carried out for the substance or the mixture

assessment: by the supplier.

SECTION 16: Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage

resulting from handling or from contact with the above product.