

**TD4819 - HEX HEAD DRILL SCREW**

**Description:**

Case Hardened Steel Hex Head Drill screw with a Bright Zinc Finish

**Finish:**

Bright Zinc Plate

**Material:**

C1022 Steel

**Additional Notes:**

EDPM bonded washers available for improved I.P protection, roofing applications and solar installation

**Standard:**

DIN7504



**OTHER ADDITIONAL INFORMATION**

Code	Size	Thread Size	Across flats of Hex	Thickness of test plates <sup>1)</sup> . in mm	Axial force in kN	Drilling speed of screw under load in min <sup>-1</sup>
TD4819	4.8 x 19	4.8	5/16" (8mm)	2 + 2 = 4	0.25	1800 to 2500
TD4825	4.8 x 25	4.8	5/16" (8mm)	2 + 2 = 4	0.25	1800 to 2500
TD4832	4.8 x 32	4.8	5/16" (8mm)	2 + 2 = 4	0.25	1800 to 2500
TD5525	5.5 x 25	5.5	5/16" (8mm)	2 + 3 = 5	0.35	1000 to 1800
TD5532	5.5 x 32	5.5	5/16" (8mm)	2 + 3 = 5	0.35	1000 to 1800
TD5538	5.5 x 38	5.5	5/16" (8mm)	2 + 3 = 5	0.35	1000 to 1800
TD5557	5.5 x 57	5.5	5/16" (8mm)	2 + 3 = 5	0.35	1000 to 1800
TD5570	5.5 x 70	5.5	5/16" (8mm)	2 + 3 = 5	0.35	1000 to 1800

