

W222-2/3/5- LEVER SPlicing CONNECTORS**Description:**

Usage: Low Voltage lighting systems, HVAC control circuits, junction boxes

Advantage: Re-usable, can accept stranded and solid & flexible wires.
ROHS Compliant

**OTHER ADDITIONAL INFORMATION**

	W222-2	W222-3	W222-5
Solid/Stranded conductor size mm²	0,08 - 2,5mm ²	0,08 - 2,5mm ²	0,08 - 2,5mm ²
Solid/Stranded conductor size AWG	28-14 AWG	28-14 AWG	28-14 AWG
Fine stranded conductor size mm²	0,08 - 4 mm ²	0,08 - 4 mm ²	0,08 - 4 mm ²
Fine stranded conductor size AWG	28-12 AWG	28-12 AWG	28-12 AWG
Rated Voltage	250v	400v	400v
Rated Inpulse voltage	4kV	4kV	4kV
Pollution Degree	2	2	2
Rated Current	32A	32A	32A
Weight	3,072g	4,153g	6,600g
Material Colour	grey	grey	grey
Connection Points	2	3	5
Number of Potentials	1	1	1
Height	14,5 mm	14,5 mm	14,5 mm
Width	12,4 mm	17 mm	26,6 mm
Depth	20,5 mm	20,5 mm	20,5 mm
Continuous Operating Temperature	85°	85°	85°

